



GORE® Filtration Products

High Durability Filter Cartridge

Spunbonded Polyester
for Food Grade Applications
271 g/m² (8 oz/yd²)

Description

A 113°C (235°F) maximum service temperature, lightweight spunbonded polyester filter cartridge for use in pulse jet style dust collectors.

Features & Benefits

- Patented GORE™ High Durability membrane technology provides an excellent combination of filtration efficiency, airflow, and durability.
- Superior alternative to paper and felt cartridges.
- Unrestrained pleat flexing during cleaning results in excellent cake release with minimal pulse energy.
- Up to three times more filter media area than felt bags and cartridges, offering higher airflow through collector.

- Available in a retrofit design to replace filter bags.
- Available in top, bottom, and horizontal loading configurations.
- Stainless steel and food grade components readily available.

Applications

- Chemicals Processing: Bin vents and nuisance dust collectors in the pharmaceutical, pigment, powder coat, plastic, and catalyst industries.
- Minerals Processing: Finish mill, nuisance, and bin vent dust collectors.
- Metals Processing: Process venting dust collectors.

Laminate Technical Data

Weight:	271 g/m ² (8 oz/yd ²)
Material:	Spunbonded Polyester
Air Permeability:	2.9 m ³ /min/m ² @ 20 mm w.g. (6 cfm/ft ² @ 0.5 w.g.)
Maximum Continuous Operating Temperature:	113°C (235°F)
Acid Resistance:	Fair
Alkali Resistance:	Fair
Mullen Burst:	2275 kPa (330 psi)
Thickness:	0.66 mm (0.026 in)
Color:	White

All data expressed as typical values. This technical data is subject to change. Please contact W. L. Gore & Associates, Inc., directly to confirm current information.

©GORE and RASTEX are registered trademarks of W. L. Gore & Associates, Inc. Patent No. 4,983,434

Rev. 04/09/07

W. L. Gore & Associates, Inc.
101 Lewisville Road, Elkton, MD 21922
Toll-Free: 1.800.431.GORE (4673)
Phone: 410.392-3300 • Fax: 410.398-6624

www.gore.com/filtration

