## **Description**

The first membrane laminate filter sock used in tubular backwash filters. It is constructed with a membrane on the outside allowing for superior filtration, excellent cake release properties, and minimal backwash volume.

## **Features & Benefits**

- GORE™ High Flow Membrane technology provides an excellent combination of filtration efficiency, liquid flow, and durability.
- Welded construction, with a unique EPDM o-ring to essentially eliminate any potential for by-passing.

## **Applications**

- White Liquor Filtration: This reduces the impact of calcium carbonate scaling on the digester liquor heaters. It also eliminates evaporate tube fouling, and reduces the cost of chemical consumption in the bleach plant.
- Weak Wash Filtration: This further reduces the amount of soda in the lime mud being fed into the lime kiln. It allows better operation of the kiln by providing a properly washed and drier cake to feed the kiln.

## **Laminate Technical Data**

Weight:	441 g/m2 (13 oz/yd²)
Fiber Content:	Fiber - Polypropylene Scrim — Polypropylene Ribbon
Felt Construction:	Supported Needlefelt
DI Water Permeability (Minimum):	3.45 m³/h @ 69 kPa (15 gpm @10 psi)
Continuous Service Temperature	94°C (200°F)
Acid Resistance:	Excellent
Alkali Resistance:	Excellent
Breaking Strength:	
Machine Direction (Average):	396 N/5 cm (90 lb/2 in) wide sample
Cross-Machine Direction (Average):	798 N/5 cm (180 lb/2 in) wide sample
Mullen Burst:	1379 kPa (200 psi)

FOR INDUSTRIAL USE ONLY. Not for use in food, drug, cosmetic or medical device manufacturing, processing, or packaging operations.

®2013 W.L. Gore & Associates, Inc. GORE™ and Designs are trademarks of W. L. Gore & Associates

