

GORE® FILTER BAGS

Polypropylene Felt 407 g/m² (12 oz/yd²)

Description

A 80 °C (176 °F) continuous service temperature, polypropylene felt filter bag for use in pulse jet style dust collectors.

Features & Benefits

- GORE membrane technology provides an excellent combination of filtration efficiency and dust cake release.
- Polypropylene fibers provide excellent acid and alkali resistance.

Applications

Used in polymers, chemicals, cement, detergent and related industries operating at low temperature requiring excellent abrasion resistance and chemical resistance.

Laminate Technical Data

Weight	407 g/m ² (12 oz/yd ²)
Fiber Content	Olefin
Felt Construction	Supported Needlefelt
Continuous Operating Temperature	80 °C (176 °F)
Maximum Surge Temperature	90 °C (194 °F)
Acid Resistance	Excellent
Alkali Resistance	Excellent
Breaking Strength	Machine Direction: 445 N/5 cm (100 lb/2 in) wide sample Cross-Machine Direction: 1113 N/5 cm (250 lb/2 in) wide sample
Mullen Burst	2068 kPa (300 psi)

All data expressed as typical values. This technical data is subject to change. Please contact W. L. Gore & Associates, Inc., directly to confirm current information.

All technical information and advice given here are based on Gore's previous experiences and/or test results. Gore gives this information to the best of its knowledge, but assumes no legal responsibility. Customers are asked to check the suitability and usability in the specific application, since the performance of the product can only be judged when all necessary operating data are available. The above information is subject to change and is not to be used for specification purposes. Gore's terms and conditions of sale apply to the sale of the products by Gore.

GORE, *Together, improving life* and designs are trademarks of W. L. Gore & Associates. © 2011–2025 W. L. Gore & Associates, Inc.