



DRIVING FUEL CELL INDUSTRY CHANGE

At Gore, we're contributing to a clean energy future by developing innovative, high-powered and reliable fuel cell components that optimize the cost of ownership in motive and stationery power generation applications.

Our path to today's clean-energy technologies began in 1969, when Bob Gore discovered expanded polytetrafluoroethylene, known as ePTFE. This versatile polymer has been advancing fuel cell technology since 1994, when we introduced our innovative ePTFE-reinforced GORE-SELECT® Membrane. Today, you'll find GORE-SELECT® Membranes at the heart of vehicle fuel cells from leading OEMs, and in other transportation, portable and stationery power applications worldwide.

Empowering the Future, Together

Decades of market experience and advanced materials expertise have enabled us to continue to advance our fuel cell industry offerings. By incorporating new-generation technologies, we've created fuel cell Proton Exchange Membranes that are more durable and higher performing.

Our proprietary technologies allow us to tailor the structure of ePTFE, creating a thinner membrane that delivers superior uniformity, high power density and greater chemical and mechanical durability. With GORE-SELECT® Membranes, our fuel cell customers enjoy a competitive advantage: they can meet their engineering targets, reduce total cost of ownership, and produce higher-performing fuel cell systems.

Gore Fuel Cell Applications

Passenger Vehicles



Remarkable journeys with zero carbon footprint

Forklifts & Materials Handling



Powering businesses with sustainable industrial energy

Trains



Connecting cities with sustainable energy

Marine



Voyage globally with cleaner energy

Commercial Vehicles



Clean, scalable solutions for mobility and logistics

Combined Heat & Power for the Home



Increasing energy efficiency for a greener lifestyle

Backup Power



Future-proof, reliable and clean energy reserves

Aviation



Powering the skies with zero pollution

GORE-SELECT® Membranes: Core Portfolio

Membrane Name	M775.15	M788.12	M765.08	M665.12
---------------	---------	---------	---------	---------

Physical Characteristics

Membrane color	Black	Clear	Clear	Clear
Orientation for use (Side not attached to backer to be used as the cathode side)	Yes	No	No	No
Nominal thickness (μm) ¹	15.5	12	8.5	12
Proton resistance (mohm*cm ²) ² 80 °C, 30% relative humidity (RH)	< 80	< 120	< 80	< 180
Hydrogen crossover (mA/cm ² /MPa) ³ 80 °C, 50% relative humidity (RH)	30	30	40	26
Tensile strength (MPa) ¹ Machine Direction (MD)	38	71	91	83
Tensile strength (MPa) ¹ Transverse Direction (TD)	39	76	96	76
Swelling ratio area change (%) ⁴	< 5	< 5	< 5	< 5
Peel strength btw. GSM and backer (mN/cm) ¹	60	50	70	70

Performance Durability

Mechanical durability Relative humidity (RH) cycle test ⁵ (normalized to M775.15)	1.0	1.3	1.1	2.5
Chemical durability OCV hold test (30% RH, 95 °C)	++	+	+	+++

Roll Properties

Standard roll widths (mm)	220 340	240 294 360 490	240 294 360 490	220 340
Standard length, Nominal at mass production (m)	200	400	400	200
Standard length, Nominal for sample roll (m) Standard A Standard B	10 50	10 50	10 50	- -
Orientation	Product in roll form is shipped with the membrane facing outwards			
Max. # membrane-to-membrane splices	1	2	2	1
Trailer length (m)	20	20	20	10
Clean room standard (ISO14644-1)	Class 7 (Class 10,000)			
Visual inspection for defects	100%			

For additional information, including product handling guidelines and safety data, please contact your local Gore representative.

1. Measurements taken with membrane conditioned to 23 °C, 50 % relative humidity (RH).
2. Proton resistance measurements taken by high frequency resistance method. Membrane impedance taken at zero imaginary impedance.
3. Hydrogen crossover measurements taken by cyclic voltammetry (CV).
4. Swelling ratio calculated by dimension change from membrane conditioned to 23 °C, 50% RH to water soaked at 100 °C for 10 min.
5. Gore original method.


For information about GORE-SELECT® Membranes M735.18 and M740.18, please contact your local Gore representative.

GORE-SELECT® Membrane Meets Fuel Cell OEM Needs

The GORE-SELECT Membrane is a proprietary Proton Exchange Membrane (PEM) that leverages our expertise in ePTFE-reinforced composite membrane technology. It enables fuel cell performance that meets OEM needs for superior uniformity, higher power density and improved chemical and mechanical durability.

High Proton Conductance & High Power Density


High Current Density Output



Thin films and superior water transport in GORE-SELECT® Membranes enable low proton resistance and therefore high power density, which offers design flexibility for the fuel cell system and stack.

Enhanced Mechanical Durability


Gore RH (Relative Humidity) Cycling Test



Our GORE-SELECT® Membrane has X-Y dimensional stability and high durability after repeated wet-dry cycles. These ePTFE-reinforced membranes far exceed the U.S. DoE performance standard for accelerated stress tests.

Balancing Performance & Durability


High Performance and Mechanical Durability



Successive generations of GORE-SELECT® Membranes have continuously improved the balance of power density and durability. This has enabled our customers to increase stack power and lifetime.

Improved Chemical Durability


Fluoride release rate in 70% RH OCV (Open Circuit Voltage) hold



Our advanced additive technology enables a long service life in harsh operating conditions. With this enhanced level of durability, engineers have the potential to push the limits of the hydrogen fuel stack design and operation even further.

Low Gas Permeance

Hydrogen Permeability



Gore's innovative reinforced membranes enables thinner designs with low gas permeation rates compared to thicker membranes. Test conditions (80°C, 50%RH)

GORE-SELECT® Membranes: Applications and Attributes

For commercial vehicles and other heavy-duty applications

M775.15 High chemical durability and high power density

For backup power, range extenders, forklifts and portable applications


M788.12 High mechanical durability and low gas permeance

For passenger vehicle applications

M765.08 High power density under dry condition

For stationary applications

M665.12 High chemical and mechanical durability for stable power generation



For information about GORE-SELECT® Membranes M735.18 and M740.18, please contact your local Gore representative.

Gore's Sustainability Commitment

Gore develops high-performing products of high societal value while meeting or exceeding applicable environmental and safety standards. As we advance our technologies and conduct our global operations, we strive to be good stewards of air, water and energy resources, and in our management of waste, through:

- Manufacturing processes that are guided by the ISO 14001 standard.
- Manufacturing processes that do not use PFOS and PFOA.
- Products that do not emit PFOS and PFOA in use.
- Products that comply with REACH Regulation (No. 1907/2006) for chemicals.
- Voluntary compliance with limit-value standards for hazardous substances under RoHS (EU Directive 2011/65/EU).
- Responsible waste management that includes precious-metals recovery, ePTFE recycling, and multiple waste-reduction streams and processes.

For more information: gore.com/about/the-gore-story/responsibility-environmental

FOR INDUSTRIAL USE ONLY. Not for use in food, drug, cosmetic or medical device manufacturing, processing, or packaging operations.

All technical information and advice given here are based on Gore's previous experiences and / or test results. Gore gives this information to the best of its knowledge, but assumes no legal responsibility. Customers are asked to check the suitability and usability in the specific application, since the performance of the product can only be judged when all necessary operating data are available. The above information is subject to change and is not to be used for specification purposes. Gore's terms and conditions of sale apply to the sale of the products by Gore.

W. L. Gore & Associates, Inc. is certified according to ISO 9001.

GORE, GORE-SELECT, *Together, improving life* and designs are trademarks of W. L. Gore & Associates. © 2024 W. L. Gore & Associates, Inc.

INTERNATIONAL CONTACTS

United States	+1 410 476 2699	China	+86 21 5172 8299	Korea	+82 2 393 3411
Germany	+49 89 4612 0	Japan	+81 3 6746 2570		

W. L. Gore & Associates, Inc.
201 Airport Road, Elkton, MD 21922
T +1 800 523 4673 F +1 410 506 8585
gore.com/clean-energy

