



Endorsed by  **De Dietrich**

GORE® GASKET TAPE SERIES 1000

Contain aggressive media, protect glass-lined steel equipment, reduce emissions

Glass-lined steel sealing challenges

Glass-lined steel equipment is used by chemical processors to deal with aggressive media under demanding conditions. Yet the inherent demands of such systems — high temperatures, alternating system pressures, limited gasket loads and deviation of sealing surfaces — can make it challenging to maintain a tight, lasting seal.

While common Polytetrafluoroethylene (PTFE) material offers good chemical resistance, it does not readily conform to flange surface deviations, nor does it resist creep particularly well under low gasket loads. Incorporating compressible materials or fillers into common envelope gaskets or filled PTFE gaskets, offers only a partial solution.

Together, improving life





Sealing challenges are even greater when gaskets for large flanges ($\geq$ DN 600/ASME 24") are fabricated offsite. This often results in long lead times, as well as shipping, handling and inventory challenges. These, along with time-consuming and complex installation procedures, can complicate turnarounds or delay start-ups.

Consequences of seal failure

Sealing with common envelope, filled PTFE or large prefabricated gaskets can be challenging — especially if there is inconsistent quality across different gasket brands or product lines. This may lead to premature gasket failure, with consequences that range from problematic to catastrophic, including:

- Leakage/emissions
- Equipment corrosion/damage
- Production downtime
- Cost increase
- Risks to personnel safety



Common envelope gaskets

GORE® Gasket Tape Series 1000 addresses all the challenges of reliably sealing large glass-lined steel flanges.


Made of 100% expanded PTFE (ePTFE), this highly conformable tape is chemically inert, and highly resistant to creep, cold flow and clamp-force loss. Its proprietary barrier core maintains an extra tight seal even at low loads.

Endorsed by De Dietrich, a leading manufacturer of glass-lined steel equipment, Series 1000 is optimized for processes utilizing highly aggressive media, as in chemical processing (e.g. specialty chemicals, agricultural products, polymers), mining and minerals. Series 1000 is designed for use in large ($\geq$ DN 600/ASME 24") or non-standard flanges typical of columns, mixer vessels, reactors, storage and receiver tanks.



GORE® Gasket Tape Series 1000

- ① Highly creep resistant, to maintain gasket load
- ② Highly conformable, to seal surface deviations
- ③ Barrier core for extra tightness at low loads
- ④ Chemically-inert 100% ePTFE protects full width of flange



A higher-performance sealing solution

Unique barrier core technology

- Barrier core engineered to amplify the available load.
- Seals more than 10 times tighter than other ePTFE gasket tapes.

Outstanding conformability to deviations


- Seals deviations even at low gasket stress.
- Easily passes the bubble test, for trouble-free mechanical completion (MC) or start-up.

Optimal form for easy handling


- Gasket can be customized on-site.
- No fabrication lead-time required.
- Convenient spool format simplifies and speeds handling & transport.
- Adhesive backing enables easy installation in ambient temperatures from 2–50 °C (36–122 °F).
- Faster, less complicated shimming tape technique for larger deviations.
- Reduces inventory costs.

Reliable and long-term seal

- Barrier core creates a tight seal that impedes even highly-permeating media.
- Provides chemical protection across the full flange width (100% ePTFE).
- Tape is engineered to resist creep and clamp-force loss.
- Allows full use of specification range of the glass-lined steel equipment.
- Enables longer maintenance cycles, as demanded by leading chemical producers.



Finite Element Analysis (FEA) model. Red indicates optimal sealing stress.



The Gore Sealant Technologies Quality Management System is certified in accordance with ISO 9001.

FOR INDUSTRIAL USE ONLY. Not for use in food, drug, cosmetic or medical device manufacturing, processing, or packaging operations.

All technical information and advice given here is based on Gore's previous experiences and/or test results. Gore gives this information to the best of its knowledge, but assumes no legal responsibility. Customers are asked to check the suitability and usability in the specific application, since the performance of the product can only be judged when all necessary operating data are available. The above information is subject to change and is not to be used for specification purposes. Gore's terms and conditions of sale apply to the sale of the products by Gore.

GORE, *Together, improving life* and designs are trademarks of W. L. Gore & Associates. © 2015–2025 W. L. Gore & Associates GmbH

PLEASE VISIT [GORE.COM/SEALANTS](https://www.gore.com/sealants) TO FIND CONTACT DETAILS FOR ALL LOCAL SALES OFFICES.

North America / South America

**W. L. Gore & Associates, Inc.
(USA)**

T +1 800 654 4229

F +1 410 506 8585

E sealants@wlgore.com

Europe / Middle East / Russia / Africa

**W. L. Gore & Associates GmbH
(Germany)**

T +49 89 4612 2215

F +49 89 4612 43780

E sealants_EU@wlgore.com

Asia / Australia

**Gore Industrial Products Trade
(Shanghai) Co., Ltd. (China)**

T +86 21 5172 8299

F +86 21 6247 9199

E sealants_AP@wlgore.com

