



GORE® Filtration Products

Case history

GORE® Low Emission Filter Bags – Titanium Dioxide

THE CHALLENGE

GORE® Acid Resistant Aramid Felt Filter Bags have been successfully used for many years in dryer baghouses across a broad range of titanium dioxide products. A new line of grades with a combination of smaller particle sizes and increased flow ability were penetrating through the stitch holes reducing product capture, increasing emissions, causing unplanned downtime and decreasing bag life.



TiO₂ particulate migration through unsealed stitch holes within 4 months of service.



THE SOLUTION

GORE® Low Emission Filter Bags were installed utilizing GORE™ Seam Tape to cover all of the stitched seams.

THE RESULT

The emissions were eliminated increasing particulate capture efficiency and productivity. Filter bag life increased from 4 to 18 months.



GORE™ Seam Tape intact after 18 months of service.



No TiO₂ particulate migration through stitch holes of the seam taped filter bag after 18 months of service.

DATA BOX

Application:	Pulse Jet Dryer Bag House
Average particle size:	0.3 microns
Operating temperature:	160 °C
Typical Production Rate:	16–20 tons/hour
Typical ACR:	2.5 fpm
Pulse Pressure:	70–80 psi

FOR INDUSTRIAL USE ONLY. Not for use in food, drug, cosmetic or medical device manufacturing, processing, or packaging options.

GORE and designs are trademarks of W. L. Gore & Associates © 2015 W. L. Gore & Associates

W. L. Gore & Associates, Inc.

101 Lewisville Road, Elkton, MD 21922

US Toll-Free: 800.431.GORE (4673)

Phone: 1.410.392.3300 • Fax: 1.410.398.6624

gore.com/filterbags

