

GORE® Coaxial Cables (50 Ohms)



Typical Applications

- Box-to-antennas
- Communications systems
- In-flight entertainment (IFE) systems
- Navigation systems

Standards Compliance

- EN4604-003: Cable Characteristics for Signal Transmission
- FAR Part 25, Appendix F, Part I: Flammability
- MIL-C-17/128: Electrical Performance Requirements for Radio Frequency, Flexible RG400 Coaxial Cable, 50 Ohms

For commercial and military aircraft systems requiring controlled impedance at 50 ohms, Gore offers a direct replacement for standard RG400 cables. Our aviation coaxial cables are proven to optimize signal transmission at speeds up to 3 GHz with 10% lower loss than RG400 cables (Table 1).

These low-loss cables yield substantial size and weight savings without losing mechanical robustness or electrical stability. Our downsized cable design is 30% smaller and 60% lighter than RG400 cables.

By replacing the RG400 version with Gore's lightweight cables in an IFE system on an Airbus 330/340 passenger airliner, the weight savings is 22 kg (48 lb). If all of the RG400 cables were replaced with our cables in a typical large cabin business jet, the expected weight savings would be approximately 19 kg (42 lb).

Table 1: Cable Properties

Electrical

Property	Value
Signal Transmission Speed GHz	Up to 3
Standard Impedance Ohms	50 ± 2
Maximum Transfer Impedance mOhm/m from 1 to 3 GHz	30
Test Voltage V AC	
Jacket Material	2000
Dielectric Material	4000
Typical Operating Voltage Vrms	250
Nominal Velocity of Propagation %	> 80
Nominal Time Delay ns/m (ns/ft)	4.0 (1.26)
Capacitance pF/m (pF/ft)	80.0 (24.4)
Nominal Dielectric Constant	1.7

Mechanical / Environmental

Property	Value
Jacket Material	Extruded FEP
Jacket Color	White (Laser Markable)
Conductor	Silver-Plated Copper
Dielectric Material	FEP over Expanded PTFE
Temperature Range °C	-65 to +200

Table 2: Cable Characteristics

Insertion loss values are based on the maximum recommended use length.

Gore Part Number	AWG Size (Stranding)	Maximum Outer Diameter mm (in)	Minimum Bend Radius mm (in)	Nominal Weight kg/km (lb/1000 ft)	Typical Insertion Loss dB/30 m (100 ft)		
					200 MHz	400 MHz	3 GHz
GSC-03-81748-00	19 (01)	3.60 (0.14)	35.0 (1.38)	2.60 (1.75)	5.1	7.5	24.0

Ordering Information

The 50-ohm version of GORE® Coaxial Cables is available in a standard size (Table 2). To place an order, contact an authorized distributor for in-stock availability at gore.com/cable-distributors. For more information or to discuss specific characteristic limits and application needs, contact a Gore representative for aerospace and defense today.

Information in this publication corresponds to W. L. Gore & Associates' current knowledge on the subject. It is offered solely to provide possible suggestions for user experimentations. It is NOT intended, however, to substitute for any testing the user may need to conduct to determine the suitability of the product for the user's particular purposes. Due to the unlimited variety of potential applications for the product, the user must BEFORE production use, determine that the product is suitable for the intended application and is compatible with other component materials. The user is solely responsible for determining the proper amount and placement of the product. Information in this publication may be subject to revision as new knowledge and experience become available. W. L. Gore & Associates cannot anticipate all variations in actual end user conditions, and therefore, makes no warranties and assumes no liability in connection with any use of this information. No information in this publication is to be considered as a license to operate under or a recommendation to infringe any patent right.

NOTICE — USE RESTRICTIONS APPLY. Not for use in food, drug, cosmetic or medical device manufacturing, processing, or packaging operations.

GORE, *Together, improving life*, and designs are trademarks of W. L. Gore & Associates. © 2025 W. L. Gore & Associates, Inc.

