



# GORE® Filtration Products

FILTER BAG

Polypropylene Felt  
407 g/m<sup>2</sup> (12 oz/yd<sup>2</sup>)

## DESCRIPTION

A 70°C (160°F) maximum service temperature, polypropylene felt filter bag for use in pulse jet style dust collectors.

## FEATURES & BENEFITS

- GORE™ membrane technology provides an excellent combination of filtration efficiency and dust cake release.
- Polypropylene fibers provide excellent acid and alkali resistance.

## LAMINATE TECHNICAL DATA

<b>Weight:</b>	<b>407 g/m<sup>2</sup> (12 oz/yd<sup>2</sup>)</b>
Fiber Content:	Olefin
Felt Construction:	Supported Needlefelt
Continuous Operating Temperature:	71°C (160°F)
Maximum Surge Temperature:	88°C (190°F)
Acid Resistance:	Excellent
Alkali Resistance:	Excellent
Breaking Strength	
• Machine Direction:	445 N/5 cm (100 lb/2 in) wide sample
• Cross-Machine Direction:	1113 N/5 cm (250 lb/2 in) wide sample
Mullen Burst:	2068 kPa (300 psi)
Thickness:	1.91 mm (0.075 in)

All data expressed as typical values. This technical data is subject to change. Please contact W. L. Gore & Associates, Inc., directly to confirm current information.

**FOR INDUSTRIAL USE ONLY.** Not for use in food, drug, cosmetic or medical device manufacturing, processing, or packaging operations.

©2010 W. L. Gore & Associates, Inc.  
©GORE-TEX, GORE, and Designs are trademarks of W. L. Gore & Associates, Inc.

**W. L. GORE & ASSOCIATES, INC.**  
101 Lewisville Road, Elkton, MD 21922  
Toll-Free: 1.800.431.GORE (4673)  
Phone: 410.392-3300 • Fax: 410.398-6624

[www.gore.com/filtration](http://www.gore.com/filtration)

